

## OS SERIES ON-BOARD TOTAL STATIONS





## **On-Board Total Stations**

- Advanced security and maintenance with TSshield™
- MAGNET® Field on-board
- Exclusive LongLink<sup>™</sup> communications
- Fast and powerful EDM
- Advanced angle accuracy

### Topcon's OS Series total stations – advanced design with superior technology

The OS is a professional grade compact total station. This advanced design provides an on-board data collection interface, exclusive LongLink™ communication, and an incredibly powerful EDM.

Work directly on the bright, color touchscreen, or with the alpha-numeric keyboard, to achieve higher levels of production with MAGNET Field on-board software. The OS total station can be used on a wide variety of applications, from building layout to earthwork volumes, and land surveying, the OS is the productive choice.

### On-board Windows® touchscreen

Running on-board software on the Windows® touchscreen computer increases productivity. The screen is large and bright, so the user can see more software functions and intuitively interact with the screen where needed. Software applications become easier to use and there is no need to hold a field controller in one hand while turning the instrument with the other. The OS has precise tangent locks to keep the angle positions accurate even with touchscreen and keyboard interaction.

Projects move faster by being able to do point collection, description entry, and on-screen calculations. The bright colorful screen provides enough resolution to view points, lines and icons, to help you make faster decisions. All of your data is stored in one spot, safely on-board.



### Exclusive LongLink™

For stakeout and other operations where being at the prism pole with a field controller is critical, Topcon's exclusive LongLink™ functionality allows you to operate a field controller more than 300 m away from the instrument. LongLink™ brings you flexibility you've never had before.





Angle Measurement	
Min. Resolution/Accuracy	
OS-101	0.5"/1"
OS-102	1"/2"
OS-103	1"/3"
OS-105	1"/5"
	Standard on 1" and 2" models
Compensation	Dual-axis compensator
Distance Measurement	
Prism EDM Range	4,000 m
Prism EDM Accuracy	2 mm + 2 ppm
Non-Prism Range	500 m

### Communications

Non-Prism

Accuracy

Measuring Time

LongLink<sup>™</sup> rover communications utilizing Bluetooth® Class 1

3 mm + 2 ppm

(0.3 - 200 m)

Fine: 0.9 sec

Rapid: 0.7 sec Tracking: 0.3 sec

USB 2.0 Slot (Host + Slave)

RS-232C Serial

Operating Temp

# General Display/Keyboard Dual LCD Touchscreen (OS-105 Single Display) Battery Operation Up to 18 hours Dust/Water Rating IP65 Wireless Bluetooth® Class 1 Connection

-30°C to 60°C\*

available

\*Special Arctic and Desert versions





Ultra-powerful, advanced EDM

Easy access USB 2.0 memory

· Compatible with industry standard

- 500 m non-prism range
- 4,000 m prism range

Up to 8 GB storageEnvironmentally protected

thumb drives

- Red/Green guidelight
- Coaxial red laser pointer
- Pinpoint, precise beamspot



### Advanced angle encoder system

- "Best in Class" 1" angle accuracy
- Incorporates exclusive IACS (Independent Angle Calibration System) on 1" and 2" models
- Self-calibration
- Proven High Accuracy Technology



### EDM trigger key

- Perfect touch location
- Promotes angle stability
- No torque when measuring on-board
- Water/Dust proof
- Easy for gloved hands



For more information: topconpositioning.com/os-series

Specifications subject to change without notice. ©2016 Topcon Corporation All rights reserved. 7010-2098 B 2/16

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license. Other trademarks and trade names are those of their respective owners.